II. CLAIM AMENDMENTS

1. (Currently amended) A method comprising:

establishing a connection between a first mobile station and a second mobile station,

transferring speech data or message data representing a first effect for stimulating an auditory or visual sense via the established connection as a ringing command;

transferring or activating data compiled from vibration effects memory, flash patterns memory or graphic objects memory for producing a second effect for stimulating a visual or tactile sense by the same established connection as a ringing command using a signaling message associated therewith,

producing the first effect for stimulating an auditory or visual sense in the second mobile station, while maintaining said connection, using a first means of expression comprising at least one element selected from the group of a loudspeaker and a display, and

producing the second effect stimulating a visual or tactile sense in the second mobile station, while maintaining said connection, using a second means of expression comprising at least one element selected from the group of a vibration unit, at least one light unit and the display, which is selected differently from the elements of the first means of expression, and wherein said second effect for stimulating a visual or tactile sense comprises a lighting effect or a vibration effect.

wherein the first effect for stimulating an auditory or visual sense and the second effect stimulating a visual or tactile sense is activated so as to be presented as a consequence of a certain user action in the second mobile terminal.

2. (Previously Presented) A method according to claim 1,

wherein establishing a connection comprises establishing a two-way telephone connection between the first mobile station and the second mobile station,

wherein transferring speech data or message data comprises transmitting data compiled from sounds memory or graphic objects memory forming the first effect for stimulating a visual or auditory sense via the telephone connection,

and wherein transferring or activating data comprises transmitting data compiled from vibration effects memory, flash patterns memory or graphic objects memory forming the second effect for stimulating a visual, or tactile sense in a User-to-User Signaling (UUS) message associated with the telephone connection.

3. (Previously Presented) A method according to claim 1.

wherein establishing a connection comprises establishing a text message connection between the first mobile station and the second mobile station, and

wherein transferring speech data or message data and transferring or activating data comprise transmitting data compiled from sounds memory, vibration effects memory, flash patterns memory or graphic objects memory forming the first and second effects in a text message.

- 4. (Previously Presented) A method according to claim 1, wherein transferring speech data or message data and transferring or activating data comprise transmitting data compiled from sounds memory, vibration effects memory, flash patterns memory or graphic objects memory forming the first and second effects in a MIDI (Musical Instrument Digital Interface) file.
- 5. (Cancelled)
- 6. (Previously Presented) A method according to claim 1, wherein the second effect further comprises a graphics effect presented on the display.
- 7. (Cancelled)
- 8. (Cancelled)
- 9. (Previously Presented) A method according to claim 1, wherein producing the second effect comprises generating a plurality of second effects for stimulating visual or tactile senses at the same time in the mobile station to form an effect entity combined from effects stimulating visual or tactile senses.

- 10. (Previously Presented) A method according to claim 1, wherein the second effect for stimulating a visual or tactile sense is activated so as to be automatically presented by the second means of expression comprising of a vibration unit, light units or a display.
- 11. (Previously Presented) A method according to claim 1, wherein the second effect for stimulating a visual or tactile sense is activated so as to be presented by the second means of expression comprising of a vibration unit, light units or a display as a consequence of certain user action.
- 12. (Previously Presented) A method according to claim 1, wherein the second effect for stimulating a visual, auditory or tactile sense is activated so as to be presented by the second means of expression comprising of a vibration unit, light units or a display when a certain start instruction is activated.
- 13. (Currently amended) A second mobile stationn apparatus comprising:

a transmitter and/or receiver for establishing a connection between a first mobile station and second mobile station,

a control unit for transferringreceiving speech data or message data of the first mobile station representing a first effect stimulating auditory or visual sense as a ringing command via the established connection;

the control unit configured for transferring or activating receiving data of the first mobile station compiled from vibration effects memory, flash patterns memory or graphic objects memory for producing a second effect stimulating a visual or tactile sense by the same established connection as the ringing command using a signaling message associated therewith,

at least one first element selected from the group of a loudspeaker and a display to present in the second mobile station, while maintaining said connection, the first effect stimulating auditory or visual sense by using the data representing the first effect, and

at least one second element selected from the group of -a vibration unit, at least one light unit and the display, which is selected different from the at least one first element, for producing in the second mobile station, while maintaining said connection, the

second effect stimulating visual, auditory or tactile sense by using the data representing the second effect, wherein said second effect for stimulating a visual or tactile sense is at least a lighting effect or a vibration effect,

wherein the first effect for stimulating an auditory or visual sense and the second effect stimulating a visual or tactile sense is activated so as to be presented as a consequence of a certain user action in the second mobile terminal.

- 14. (Currently amended) The apparatus The second mobile station of claim 13, further comprising a sounds unit, a sounds controller, and a sounds memory for controlling sound effects.
- 15. (Currently amended) The apparatus The second mobile station of claim 13, further comprising a vibration unit, a vibrator controller, and a vibration effects memory for controlling vibration effects.
- 16. (Currently amended) The <u>apparatus second mobile station</u> of claim 13, further comprising light units, a lighting controller, and a flash patterns memory for controlling lighting effects.
- 17. (Currently amended) The <u>second mobile station</u>apparatus of claim 13, further comprising a display, a display controller, and a graphic objects memory for controlling visual effects.
- 18. (Currently amended) The <u>second mobile station</u> apparatus of claim 13, wherein the first or second element comprises a loudspeaker, a sounds unit, a vibration unit, light units or a display for presenting effects simultaneously as an effect entity combined from effects stimulating visual, auditory or tactile sense.
- 19. (Currently amended) The <u>apparatus second mobile station</u> of claim 13, wherein the control unit is configured for downloading a MIDI file for accessing the effect entity.
- 20. (Currently amended) The apparatus of claim 13claim 31, wherein the <u>first</u> control unit is configured for transmitting effects to be presented on a second mobile station.

- 21. (Currently amended) The apparatus of claim 20, wherein the <u>first</u> control unit is configured for transmitting effects to a second mobile station as part of a text message.
- 22. (Currently amended) The apparatus of claim 20, wherein the <u>first</u> control unit is configured for transmitting effects to a second mobile station during a telephone connection using a User-to-User Signaling (UUS) message associated with the telephone connection.
- 23. (Currently amended) The apparatus of claim 21, characterized in that wherein the mobile station apparatus comprises means for activating effects automatically.
- 24. (Currently amended) The apparatus of claim 21, characterized in that wherein the mobile station apparatus comprises means for activating effects as a consequence of user action.
- 25. (Currently amended) The apparatus of claim 23, wherein the <u>first_control_unit_or_the</u> second control_unit_is configured for activating effects to be presented when a certain start instruction is activated.
- 26. (Previously Presented) A method according to claim 1, wherein producing the second effect comprises transmitting data compiled from sounds memory, vibration effects memory, flash patterns memory or graphic objects memory for activating a second effect stimulating visual, auditory or tactile sense via the same established connection.
- 27. (Currently amended) The <u>second mobile stationapparatus</u> of claim 14, wherein the <u>first</u> control unit is configured for transmitting data compiled from sounds memory, vibration effects memory, flash patterns memory or graphic objects memory for activating a second effect stimulating visual, auditory or tactile sense via the same established connection.
- 28. (Previously Presented) A method according to claim 1, wherein said established connection is a voice call.
- 29. (Currently amended) The <u>second mobile stationapparatus</u> of claim 13, wherein said established connection is a voice call.
- 30. (Previously Presented) A method according to claim 6, wherein the graphics effect comprises an animation or an image.

31. (New) An apparatus comprising:

a transmitter and/or receiver for establishing a connection between a first mobile station of said apparatus and a second mobile station of said apparatus,

a first control unit for transferring speech data or message data of the first mobile station representing a first effect stimulating auditory or visual sense as a ringing command via the established connection;

the first control unit for transferring data of the first mobile station compiled from vibration effects memory, flash patterns memory or graphic objects memory for producing a second effect stimulating a visual or tactile sense by the same established connection as the ringing command using a signaling message associated therewith,

a second control unit for receiving speech data or message data of the first mobile station in the second mobile station representing a first effect stimulating auditory or visual sense as a ringing command via the established connection;

the second control unit for receiving data of the first mobile station in the second mobile station compiled from vibration effects memory, flash patterns memory or graphic objects memory for producing a second effect stimulating a visual or tactile sense by the same established connection as the ringing command using a signaling message associated therewith,

at least one first element selected from the group of a loudspeaker and a display to present in the second mobile station, while maintaining said connection, the first effect stimulating auditory or visual sense by using the data representing the first effect, and

at least one second element selected from the group of a vibration unit, at least one light unit and the display, which is selected different from the at least one first element, for producing in the second mobile station, while maintaining said connection, the second effect stimulating visual, auditory or tactile sense by using the data representing the second effect, wherein said second effect for stimulating a visual or tactile sense is at least a lighting effect or a vibration effect,

wherein the first effect for stimulating an auditory or visual sense and the second effect stimulating a visual or tactile sense is activated so as to be presented as a consequence of a certain user action in the second mobile terminal.

32. (New) A second mobile station comprising:

means for establishing a connection between a first mobile station and second mobile station,

means for receiving speech data or message data of the first mobile station representing a first effect stimulating auditory or visual sense as a ringing command via the established connection;

means for receiving data of the first mobile station compiled from vibration effects memory, flash patterns memory or graphic objects memory for producing a second effect stimulating a visual or tactile sense by the same established connection as the ringing command using a signaling message associated therewith,

means selected from the group of a loudspeaker and a display to present in the second mobile station, while maintaining said connection, the first effect stimulating auditory or visual sense by using the data representing the first effect, and

means selected from the group of a vibration unit, at least one light unit and the display, which is selected different from the at least one means selected from the group, for producing in the second mobile station, while maintaining said connection, the second effect stimulating visual, auditory or tactile sense by using the data representing the second effect, wherein said second effect for stimulating a visual or tactile sense is at least a lighting effect or a vibration effect,

wherein the first effect for stimulating an auditory or visual sense and the second effect stimulating a visual or tactile sense is activated so as to be presented as a consequence of a certain user action in the second mobile terminal.

33. (New) An apparatus comprising:

means for establishing a connection between a first mobile station of said apparatus and a second mobile station of said apparatus,

means for transferring speech data or message data of the first mobile station representing a first effect stimulating auditory or visual sense as a ringing command via the established connection;

means for transferring data of the first mobile station compiled from vibration effects memory, flash patterns memory or graphic objects memory for producing a second effect stimulating a visual or tactile sense by the same established connection as the ringing command using a signaling message associated therewith,

means for receiving speech data or message data of the first mobile station in the second mobile station representing a first effect stimulating auditory or visual sense as a ringing command via the established connection;

means for receiving data of the first mobile station in the second mobile station compiled from vibration effects memory, flash patterns memory or graphic objects memory for producing a second effect stimulating a visual or tactile sense by the same established connection as the ringing command using a signaling message associated therewith,

means selected from the group of a loudspeaker and a display to present in the second mobile station, while maintaining said connection, the first effect stimulating auditory or visual sense by using the data representing the first effect, and

means selected from the group of a vibration unit, at least one light unit and the display, which is selected different from the at least one means selected from the group, for producing in the second mobile station, while maintaining said connection, the second effect stimulating visual, auditory or tactile sense by using the data representing the second effect, wherein said second effect for stimulating a visual or tactile sense is at least a lighting effect or a vibration effect,

wherein the first effect for stimulating an auditory or visual sense and the second effect stimulating a visual or tactile sense is activated so as to be presented as a consequence of a certain user action in the second mobile terminal.